



product description

The PR series is an exceptional model in appearance and performance suited for cooling, heating and ventilating applications. The model PR-3 & 4 is a return air unit designed for surface mount applications for plaster or similar type mounting surfaces for round or square ducts respectively. All exposed surfaces are of aluminum con-

struction with the rear plenum being galvanized steel. The face is easily removable allowing access for duct connection. The model is available with a round, square or rectangular neck. Square opposed blade and round butterfly dampers are available for volume control where applicable. White finish is standard.

nomenclature for perforated products

- P = Perforated Diffuser
- R = Return
- S = Supply
- 1 = Round neck to fit 24" x 24" Grid - Standard T-Bar
- 2 = Square neck to fit 24" x 24" Grid - Standard T-Bar
- 10 = Round neck to fit 24" x 48" Grid - Standard T-Bar
- 20 = Square neck to fit 24" x 48" Grid - Standard T-Bar
- BFD = Butterfly damper used with round neck diffusers
- OB = Opposed blade damper used with square neck diffusers
- FGB = Fiberglass back diffusers
- NRF = Non-removable face
- PCRT = 22" x 22" and 46" x 22" sizes are suitable for 24" x 24" and 48" x 24" grid. Removable face with duct connection.
- P(S) or P(R)-3 = Round neck - surface mount for plaster or similar surface
- P(S) or P(R)-4 = Square neck - surface mount for plaster or similar surface
- P(S) or P(R)-5 = Round neck - spline mount (spline on two opposite sides)
- P(S) or P(R)-6 = Square neck - spline mount (spline on two opposite sides)
- P(S) or P(R)-7 = Round neck - spline mount with locking device
- P(S) or P(R)-8 = Square neck - spline mount with locking device
- P(S) or P(R)-11 = Round neck - tegular mount
- P(S) or P(R)-12 = Square neck - tegular mount

NOTE: All round neck prices are for diameters 4", 5", 6", 7", 8", 9", 10", 12", 14" and 16"

AIRGUIDE MANUFACTURING
795 WEST 20TH STREET
HIALEAH, FLORIDA 33010
PHONE: (305) 888-1631