



**ACCESSORIES**

OPPOSED BLADE DAMPER

**MODELS: OB, OB-L, OB-FL**

**SUSTAINABLE EXTRUDED ALUMINUM**

**Dimensions are in inches**

	<p><b>OB</b></p> <p>Opposed blade damper .</p>			
	<p><b>OB-L</b></p> <p>Opposed blade damper with legs.</p>			
	<p><b>OB-FL</b></p> <p>Opposed blade damper with fire link.</p>			
<p><b>DESCRIPTION:</b></p> <ol style="list-style-type: none"> <li>1. The model OB is 6063 extruded aluminum alloy construction and utilizes nylon bushings where the blades meet the frame to eliminate corrosion and vibration. The unit is used in conjunction with all products. it is screwdriver-operated and allows for precise balancing with minimum leakage.</li> <li>2. The model OB-L is identical to OB with the exception that the unit has four or more legs for duct mounting.</li> <li>3. The model OB-FL is identical to OB with the exception that a UL-approved fire links is mounted to the frame of the unit that automatically springs the blades closed without having any interference by the fire link assembly.</li> </ol>				
<p><b>PROJECT:</b></p>				
<p><b>ENGINEER:</b></p>	<table border="1"> <tr> <td data-bbox="1003 1900 1149 1948">DATE</td> <td data-bbox="1149 1900 1328 1948">SERIES</td> <td data-bbox="1328 1900 1567 1948">DRAWING NO.</td> </tr> </table>	DATE	SERIES	DRAWING NO.
DATE	SERIES	DRAWING NO.		
<p><b>CONTRACTOR:</b></p>	<table border="1"> <tr> <td data-bbox="1003 1948 1149 1995"></td> <td data-bbox="1149 1948 1328 1995"></td> <td data-bbox="1328 1948 1567 1995"></td> </tr> </table>			