



**OUTSIDE AIR LOUVERS**

2" OUTSIDE AIR LOUVERS

**MODELS: OL-2-FLANGE-J, OL-2-FLANGE-CHEVRON**

**SUSTAINABLE EXTRUDED ALUMINUM**

**Dimensions are in inches**

		<p><b>OL-2-FLANGE-J</b></p> <p>Outside air louvers with "J" blades and flange frame.</p>
--	--	--

		<p><b>OL-2-FLANGE-CHEVRON</b></p> <p>Outside air louvers with chevron blades and flange frame.</p>
--	--	--

<p><b>DESCRIPTION:</b></p> <ol style="list-style-type: none"> <li>1. "J" Blade: 6063 extruded aluminum alloy. It utilizes a flange frame with a "J" configuration blade which is 2" deep and mounted 1" on center.</li> <li>2. Chevron Blade: Same as flange "J" except that the chevron blade provides a sight-proof appearance.</li> <li>3. An .080" aluminum extrusion is used for maximum strength with mechanically joined frame. It is weather resistant and neat in appearance. A factory-installed drain hole at the bottom of the frame allows water drainage.</li> <li>4. 30" maximum one-piece construction for "J" blade. 36" maximum one-piece construction for chevron blade. A 72" maximum height applies to this product. An I-beam is furnished as a connecting mullion for multiple piece units.</li> </ol>	<p><b>OPTIONS:</b></p> <p>1. Finish</p> <ul style="list-style-type: none"> <li><input type="checkbox"/> White</li> <li><input type="checkbox"/> ANOD Clear Anodized</li> <li><input type="checkbox"/> Medium Bronze</li> <li><input type="checkbox"/> Black</li> <li><input type="checkbox"/> Custom _____</li> </ul> <p>2. Options</p> <ul style="list-style-type: none"> <li><input type="checkbox"/> OBFL (Fire link)</li> <li><input type="checkbox"/> Expanded Aluminum Bird Screen</li> <li><input type="checkbox"/> Woven Fiberglass Insect Screen</li> <li><input type="checkbox"/> Filter Frame</li> <li><input type="checkbox"/> Opposed Blade Damper</li> </ul>
---	--

<b>PROJECT:</b>			
<b>ENGINEER:</b>	<b>DATE</b>	<b>SERIES</b>	<b>DRAWING NO.</b>
<b>CONTRACTOR:</b>			